

## High Power LED

BL-HP15EXX

### Features:

- Ø 10W LEDs suitable for illumination lamps and decorative lighting
- Ø Longer service and less luminosity loss, 50,000hours
- Ø Different emitting colors are available
- Ø Lambertian, batwing and side emitting are all available

### Applications:

Commercial lighting  
Residential lighting  
Decorative lighting



**1Watt Lambertian**


### Electrical-optical characteristics: (Ta=25°C)

Part Number	Chip		Lens Type	Forward Voltage(VF) Unit: V		Flux Unit:lm		Viewing Angle 2θ/2 (deg)
	Emitted Color	λ <sub>p</sub> (nm) or CTT		Typ	Max	Min.	Typ.	
				Water Clear				
BL-HP15EUEC	Ultra Orange	630		6.5	7.0	200	300	
BL-HP15EUYC	Ultra Yellow	590		6.5	7.0	200	300	
BL-HP15EPGC	Ultra Pure Green	525		10	11	400	500	
BL-HP15EBGC	Ultra Bluish Green	505		10	11	350	450	
BL-HP15EUBC	Ultra Blue	470		10	11	100	150	
BL-HP15EUWC	Ultra White	6000k		10	11	400	500	
BL-HP15EUW2C	Ultra Warm White	3200k		10	11	300	400	

### Absolute maximum ratings (Ta=25°C)

Parameter	UE	UY	BG	PG	UB	UW	Unit
Forward Current I <sub>F</sub>	1200	1200	1000	1000	1000	1000	mA
LED Junction Temperature	120	120	120	120	120	120	°C
Peak Forward Current I <sub>PF</sub> (Duty 1/10 @1KHZ)	2000	2000	2000	2000	2000	2000	mA
Operation Temperature T <sub>OPR</sub>	-40 to +80						°C
Storage Temperature T <sub>STG</sub>	-40 to +100						°C
Aluminum-Core Pcb Temperature	105						°C

Package configuration & Internal circuit diagram




Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is 0.25(0.01")unless otherwise noted.
3. Specifications are subject to change without notice.


# High Power LED

**BL-HP15EXX**


## Typical electrical-optical characteristics curves:




- (1) - GaAsP/GaAs 655nm/Red
- (2) - GaP 570nm/Yellow Green
- (3) - GaAsP/GaP 585nm/Yellow
- (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red
- (5) - GaP 700nm/Bright Red
- (6) - GaAlAs/GaAs 660nm/Super Red
- (8) - GaAsP/GaP 610nm/Super Red
- (9) - GaAlAs 880nm
- (10) - GaAs/GaAs & GaAlAs/GaAs 940nm
- (A) - GaN/SiC 430nm/Blue
- (B) - InGaN/SiC 470nm/Blue
- (C) - InGaN/SiC 505nm/Ultra Green
- (D) - InGaAlSiC 525nm/Ultra Green




FORWARD VOLTAGE (V)  
FORWARD CURRENT VS.  
FORWARD VOLTAGE





FORWARD CURRENT (mA)  
RELATIVE LUMINOUS  
INTENSITY VS. FORWARD  
CURRENT



AMBIENT TEMPERATURE Ta ( )  
FORWARD CURRENT VS. AMBIENT  
TEMPERATURE



AMBIENT TEMPERATURE Ta ( )



NOTE:25 free air temperature unless otherwise specified

High Power LED

BL-HP15EXX

Packing and weighting

