

Rectangular Type, BI-COLOR LED lamp

BL-L2349

Features:

- 2*3*4mm Rectangular Type BI-COLOR LED Lamps, with 3 leads
- Ultra brightness.
- Choice of various viewing angles.
- Diffused, Transparent and Water clear lens are available.
- IC compatible /Low current capability.
- RoHs Compliance



■ Electrical-optical characteristics: (Ta=25°C) (Test Condition: IF=20mA)

Part Number	Chip			Lens Type	Forward Voltage(VF) Unit:V		Luminous Intensity (Iv) Unit:mcd		Viewing Angle 2θ1/2(deg)
	Emitted Color	Material	λ _P (nm)		Typ	Max	Min.	Typ	
BL-L2349EGW	Red	GaAsP/GaP	635	Water Diff.	2.10	2.50	5	20	60
	Green	GaP/GaP	570		2.20	2.50	3	15	
BL-L2349SGW	Hi Red	AlGaAs,SH	660		1.85	2.20	5	20	
	Green	GaP/GaP	570		2.20	2.50	3	15	
BL-L2349YGW	Yellow	GaAsP/GaP	585		2.10	2.50	3	15	
	Green	GaP/GaP	570		2.20	2.50	3	15	
BL-L2349UEUGW	Ultra Yellow	AlGaInP	630		2.10	2.50	90	180	
	Ultra Green	AlGaInP	574		2.20	2.50	70	120	


■ Absolute maximum ratings (Ta=25°C)

Parameter	E/ S	UE	Y	G	UG	Unit
Forward Current I_F	25	30	25	30	30	mA
Power Dissipation P_d	60	65	60	65	75	mW
Reverse Voltage V_R	5	5	5	5	5	V
Peak Forward Current I_{PF} (Duty 1/10 @1KHZ)	150	150	150	150	150	mA
Operation Temperature T_{OPR}	-40 to +80					°C
Storage Temperature T_{STG}	-40 to +85					°C
Lead Soldering Temperature T_{SOL}	Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)					°C

Rectangular Type, BI-COLOR LED lamp

BL-L2349

■ Package configuration & Internal circuit diagram




Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is $\pm 0.25(0.01")$ unless otherwise noted.
3. Specifications are subject to change without notice.


Rectangular Type, BI-COLOR LED lamp

BL-L2349


■ Typical electrical-optical characteristics curves:




- | | |
|---|--------------------------------------|
| (1) - GaAsP/GaAs 655nm/Red | (9) - GaAlAs 880nm |
| (2) - GaP 570nm/Yellow Green | (10) - GaAs/GaAs & GaAlAs/GaAs 940nm |
| (3) - GaAsP/GaP 585nm/Yellow | (A) - GaN/SiC 430nm/Blue |
| (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red | (B) - InGaN/SiC 470nm/Blue |
| (5) - GaP 700nm/Bright Red | (C) - InGaN/SiC 505nm/Ultra Green |
| (6) - GaAlAs/GaAs 660nm/Super Red | (D) - InGaAl/SiC 525nm/Ultra Green |
| (8) - GaAsP/GaP 610nm/Super Red | |




FORWARD VOLTAGE (Vf)
FORWARD CURRENT VS.
FORWARD VOLTAGE





FORWARD CURRENT (mA)
RELATIVE LUMINOUS
INTENSITY VS. FORWARD
CURRENT



AMBIENT TEMPERATURE Ta(°C)
FORWARD CURRENT VS. AMBIENT
TEMPERATURE



AMBIENT TEMPERATURE Ta(°C)



NOTE: 25°C free air temperature unless otherwise specified

Rectangular Type, BI-COLOR LED lamp

BL-L2349

■ Packing and weighting

